



Bearing numbers	Boundary dimensions(mm)						Basic load ratings(KN)		Weight Kg
	d	D	t	b	c	r/min	Cr	Cor	
32005	25	47	15	15	11.5	0.6	27.8	33.5	0.114
32006	30	55	17	17	13	1	37.5	46	0.166
32007	35	62	18	18	14	1	41.5	52.5	0.224
32008	40	68	19	19	14.5	1	50	65.5	0.273
32009	45	75	20	20	15.5	1	57.5	76.5	0.346
32010	50	80	20	20	15.5	1	62.5	88	0.366
32011	55	90	23	23	17.5	1.5	80.5	118	0.563
32012	60	95	23	23	17.5	1.5	82	123	0.576
32013	65	100	23	23	17.5	1.5	83	128	0.630
32014	70	110	25	25	19	1.5	105	160	0.848
32015	75	115	25	25	19	1.5	106	167	0.909
32016	80	125	29	29	22	1.5	139	216	1.28
32017	85	130	29	29	22	1.5	142	224	1.58
32018	90	140	32	32	24	2	168	270	1.79
32019	95	145	32	32	24	2	171	280	1.83
32020	100	150	32	32	24	2	170	281	1.91
32021	105	160	35	35	26	2.5	201	335	2.42
32022	110	170	38	38	29	2.5	236	390	3.07
32205	25	52	19.25	18	16	1	42	47	0.187
32206	30	62	21.25	20	17	1	54.5	64	0.301
32207	35	72	24.25	23	19	1.5	72.5	87	0.457
32208	40	80	24.75	23	19	1.5	79.5	93.5	0.558
32209	45	85	24.75	23	19	1.5	82	100	0.607
32210	50	90	24.75	23	19	1.5	87.5	109	0.648
32211	55	100	26.75	25	21	2	108	134	0.876
32212	60	110	29.75	28	24	2	130	164	1.18
32213	65	120	32.75	31	27	2	159	206	1.58
32214	70	125	33.25	31	27	2	166	220	1.68
32215	75	130	33.25	31	27	2	168	224	1.74
32216	80	140	35.25	33	28	2.5	199	265	2.18
32217	85	150	38.5	36	30	2.5	224	300	2.75
32218	90	160	42.5	40	34	2.5	262	360	3.49
32219	95	170	45.5	43	37	3	299	415	4.30
32220	100	180	49	46	39	3	330	465	5.12
32305	25	62	25.25	24	20	1.5	61.5	64.5	0.381
32306	30	72	28.75	27	23	1.5	81	90	0.583
32307	35	80	32.75	31	25	2	101	115	0.787
32308	40	90	35.25	33	27	2	122	150	1.08
32309	45	100	38.25	36	30	2	154	191	1.46
32310	50	110	42.25	40	33	2.5	184	232	1.92
32311	55	120	45.5	43	35	2.5	215	275	2.44
32312	60	130	48.5	46	37	3	244	315	3.02
32313	65	140	51	48	39	3	273	350	3.66
32314	70	150	54	51	42	3	310	405	4.46
32315	75	160	58	55	45	3	355	470	5.35
32316	80	170	61.5	58	48	3	395	525	6.41
32317	85	180	63.5	60	49	4	405	525	7.15
32318	90	190	67.5	64	53	4	450	595	8.57
32319	95	200	71.5	67	55	4	505	670	10.10
32320	100	215	77.5	73	60	4	570	770	12.7
32321	105	225	81.5	77	63	4	610	825	14.5