



Bearing numbers	Boundary dimensions				Basic load ratings(KN)		Weight Kg
	d	D	B	ra/a	Cr	Cor	
2204	20	47	18	1	12.6	3.3	0.140
2205	25	52	18	1	12.3	3.45	0.157
2206	30	62	20	1	15.2	4.5	0.256
2207	35	72	23	1.1	21.5	6.6	0.392
2208	40	80	23	1.1	22.5	7.35	0.433
2209	45	85	23	1.1	23.2	8.15	0.500
2210	50	90	23	1.1	23.2	8.45	0.583
2211	55	100	25	1.5	26.5	9.9	0.787
2212	60	110	28	1.5	34.0	12.6	1.08
2213	65	120	31	1.5	43.5	16.4	1.44
2214	70	125	31	1.5	44.0	17.1	1.52
2215	75	130	31	1.5	44.5	17.8	1.58
2216	80	140	33	2	48.5	19.9	1.99
2217	85	150	36	2	58.0	23.6	2.54
2218	90	160	40	2	70.0	28.7	3.19
2219	95	170	43	2.1	83.5	34.5	3.89
2220	100	180	46	2.1	94.0	38.5	4.65
2305	25	62	24	1.1	24.4	6.6	0.334
2306	30	72	27	1.1	31.5	8.75	0.496
2307	35	80	31	1.5	38.5	11.2	0.671
2308	40	90	33	1.5	45.0	13.5	0.928
2309	45	100	36	1.5	54.0	16.7	1.23
2310	50	110	40	2	64.5	20.2	1.63
2311	55	120	43	2	75.5	24.0	2.10
2312	60	130	46	2.1	87.0	28.2	2.59
2313	65	140	48	2.1	96.0	32.5	3.20
2314	70	150	51	2.1	109	37.3	3.92
2315	75	160	55	2.1	123	43.0	4.78
2316	80	170	58	2.1	128	45.0	5.65
2317	85	180	60	3	140	51.5	6.55
2318	90	190	64	3	152	57.5	7.75
2319	95	200	67	3	165	64.5	9.05
2320	100	215	73	3	192	79	11.5
2321	105	225	77	3	205	87	13.3
2322	110	240	80	3	217	94.5	15.8